


Eco i5.1

OD-3R



1200 x 1000 mm







1	Technical Data	Bottom support	Top Deck	Dimensions (mm)	Maximum Load	Capacities (kg)	Weight (kg)	
					Static	Dynamic	Racking	PP
	Eco i5.1 (OD-3R)	3 runners	open	1200 x 1000 x 155	4000	1500	1000	14,0

Entry: 4 ways | Nesting height: - mm | Safety rim: 6,5 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40′ HC Container	
Logistic Data	stack	total	stack	total	stack	total	stack	total	stack	total
Eco i5.1 (OD-3R)	15	390	-	-	18	468	15	390	16	352

3enefits

- . High performance at low cost.
- 2. Monoblock design with impressive weight/load ratio.
- 3. Ideal for closed loops, distribution, production areas and export.
- 4. Strong performance with roller conveyors and in high racks.
- 5. Flow-through block design ensures effective cleaning and quick drying.
- 6. Rounded corners to reduce potential fork access damage.
- 7. Reusable pallet made of recycled plastic and 100% recyclable

on

- 1. Safety rim.
- 2. Anti slip strips and grommets on and under deck.
- 3. RFID transponders and other IoT options.
- 4. Specific colors on request.
- 5. Individual marking and labelling.
- 6. ESD: anti-static.