


Eco i5.1

OD-5R



1200 x 1000 mm







| Technical Data | Bottom support | Top Deck | Dimensions (mm) | Maximum Load | Capacities (kg) | Weight (kg) | |
|------------------|-------------------|----------|-------------------|--------------|-----------------|-------------|------|
| | | | | Static | Dynamic | Racking | PP |
| Eco i5.1 (OD-5R) | 5 runners | open | 1200 x 1000 x 155 | 4000 | 1500 | 1000 | 15,0 |

Entry: 4 ways | Nesting height: - mm | Safety rim: 6,5 mm

| Logistic Data | Standard Truck Europe | | Standard Truck USA | | Mega Truck | | Jumbo Truck | | 40´ HC Container | |
|------------------|-----------------------|-------|--------------------|-------|------------|-------|-------------|-------|------------------|-------|
| | stack | total | stack | total | stack | total | stack | total | stack | total |
| Eco i5.1 (OD-5R) | 15 | 390 | - | - | 18 | 468 | 15 | 390 | 16 | 352 |

3enefits

- 1. High performance at low cost
- 2. Monoblock design with impressive weight/load ratio
- 3. Ideal for closed loops, distribution, production areas and export
- 4. Strong performance with roller conveyors and in high racks
- 5. Flow-through block design ensures effective cleaning and quick drying
- 6. Rounded corners to reduce potential fork access damage
- 7. Reusable pallet made of recycled plastic and 100% recyclable

ions

- 1. Safety rim
- 2. Anti slip strips and grommets on and under deck
- 3. RFID transponders and other IoT options
- 4. Specific colors on request
- 5. Individual marking and labelling
- 6. ESD: anti-static