


Endur C7.2

OD-3R


1140 x 1140 mm



Technical Data	Bottom support	Top Deck	Dimensions (mm)	Maximum Load Capacities (kg)			Weight (kg)	
				Static	Dynamic	Racking	PP	PE Mix
Endur C7.2 (OD-3R)	3 runners	open	1140 x 1140 x 165	5000	2500	1250	23,5	24,5

Entry: 4 ways | Nesting height: - mm | Safety rim: 7 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40' HC Container	
	stack	total	stack	total	stack	total	stack	total	stack	total
Endur C7.2 (OD-3R)	15	330	-	-	18	382	18	432	16	330

Benefits

1. Developed for transport in ISO freight containers
2. Robust design to maximize inherent impact resistance
3. Ability to carry loads up to 1250 kg in the high rack
4. Ideal for use in automated conveyor systems
5. Various anti-slip options are available
6. Reusable pallet made of recycled plastic and 100% recyclable

Options

1. Safety rims
2. Anti-slip strips on deck and grommets under deck
3. RFID transponders and other IoT options
4. Specific colors on request
5. Individual marking and labeling
6. ESD: conductive and anti-static
7. Further bottom version: 6 runners
8. Also available with closed deck