



Endur i5

CD-3R


1200 x 1000 mm



| Technical Data | Bottom support | Top Deck | Dimensions (mm) | Maximum Load Capacities (kg) | | | Weight (kg) |
|------------------|----------------|----------|-------------------|------------------------------|---------|---------|-------------|
| | | | | Static | Dynamic | Racking | PE |
| Endur i5 (CD-3R) | 3 runners | closed | 1211 x 1014 x 154 | 5000 | 2000 | 700 | 20,0 |

Entry: 4 ways | Nesting height: - mm | Safety rim: 20 mm

| Logistic Data | Standard Truck Europe | | Standard Truck USA | | Mega Truck | | Jumbo Truck | | 40' HC Container | |
|------------------|-----------------------|-------|--------------------|-------|------------|-------|-------------|-------|------------------|-------|
| | stack | total | stack | total | stack | total | stack | total | stack | total |
| Endur i5 (CD-3R) | 15 | 390 | - | - | 17 | 442 | 17 | 476 | 16 | 342 |

Benefits

1. Designed with extra high safety rim
2. The rim is slightly set outward so that boxes can be placed within the rim and be transported safely
3. Excellent performance for applications with a high circulation rate
4. Ideal for the automotive industry
5. The safety rim ensures easy transportation of empty pallet stacks
6. The high-quality design makes the pallet extremely strong and guarantees a long lifetime
7. Reusable pallet made of recycled plastic and 100% recyclable

Options

1. RFID transponders and other IoT options
2. Specific colors on request
3. Individual marking and labelling