











Eco E5.2

OD-3R-3M

1200 x 800 mm







| Technical Data | Bottom support | Top Deck | Dimensions (mm) | Maximum Load Capacities (kg) | | | | Weight (kg) | |
|---------------------|-------------------|----------|------------------|------------------------------|---------|---------|------|-------------|--|
| | | | | Static | Dynamic | Racking | PE | PE Mix | |
| Eco E5.2 (OD-3R-3M) | 3 runners | open | 1200 x 800 x 150 | 4000 | 2000 | 1250 | 15,5 | 16 | |

Entry: 6 ways | Nesting height: - mm | Safety rim: 7 / 22 mm

| Logistic Data | Standard Truck Europe | | Standard Truck USA | | Mega Truck | | Jumbo Truck | | 40´ HC Container | |
|---------------------|-----------------------|-------|--------------------|-------|------------|-------|-------------|-------|------------------|-------|
| | stack | total | stack | total | stack | total | stack | total | stack | total |
| Eco E5.2 (OD-3R-3M) | 16 | 528 | - | - | 19 | 627 | 19 | 722 | 16 | 400 |

3enefits

- Versatile plastic pallet in EUR footprint with metal reinforcements designed to maximize performance at low cost
- 2. Monoblock design with impressive weight/load ratio
- 3. Excellent impact resistance thanks to wavy design
- Ideal for both closed loops and export applications, with corresponding material choice
- 5. Strong performance with roller conveyors and in high racks
- 6. Rounded corners to reduce potential fork damages
- 7. Protected RFID label through special RFID pocket
- 8. Compatible with Eco E5 and Eco E7
- 9. Reusable pallet made of recycled plastic and 100% recyclable

- 1. Safety rims (7 mm internal rim or 22 mm external rim)
 - 2. Grommets on and under deck
- 3. RFID transponders and other IoT options
- 4. Specific colors on request
- 5. Individual marking and labeling
- 6. Also available without metal reinforcement