


# Eco i5.2

## OD-3R

1200 x 1000 mm



Technical Data	Bottom support	Top Deck	Dimensions (mm)	Maximum Load Capacities (kg)			Weight (kg)	
				Static	Dynamic	Racking	PE	PE Mix
Eco i5.2 (OD-3R)	3 runners	open	1200 x 1000 x 150	4000	2000	1000*	15	15,5

Entry: 4 ways | Nesting height: - mm | Safety rim: 7 / 22 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40' HC Container	
	stack	total	stack	total	stack	total	stack	total	stack	total
Eco i5.2 (OD-3R)	16	416	-	-	19	494	19	532	16	352

### Benefits

- Versatile plastic pallet in industrial footprint designed to maximize performance at low cost
- Excellent impact resistance thanks to wavy design
- Monoblock design with impressive weight/load ratio
- Ideal for both closed loops and export applications
- Strong performance with roller conveyors and in high racks
- Rounded corners to reduce potential fork damages
- Protected RFID label through special RFID pocket
- Compatible with Eco i5 and eco i7
- Reusable pallet made of recycled plastic and 100% recyclable

### Options

- Safety rims of 7 or 22 mm
- Grommets on and under deck
- RFID transponders and other IoT options
- Specific colors on request
- Individual marking and labeling
- ESD prevention: anti-static
- Also available with metal reinforcement
- Also available with 5 runners

\*Load specifications apply only for racking on the LS. For SS racking: 750Kg.

Technical data are guideline values based on experience and tests according to ISO 8611 with evenly distributed loads at 20°C. The data may vary based on intended use, product features, raw materials used and environmental influences. Upon request our sales team will confirm the data required for your individual application.