









## **Endur S7**

OD-6R















47.2 x 47.2 in 1200 x 1200 mm

Technical Data	Bottom support	Top Deck	Dimensions (in) / (mm)	Maximum Load Capacities (lbs) / (kg)				Weight (lbs) / (kg)		
				Static	Dynamic	Racking	PE	PP	PP Mix	
Endur S7 (OD-6R)	6 runners	open	47.2 x 47.2 x 6.5	11000	5500	3000	-	62.0	64.0	
			1200 x 1200 x 165	5000	2500	1375	29,0	28,0	-	

Entry: 4 ways | Nesting height: - inch / - mm | Safety rim: 0.3 in / 7 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40′ HC Container	
	stack	total	stack	total	stack	total	stack	total	stack	total
Endur S7 (OD-6R)	15	330	-	-	18	396	18	432	16	265

- Robust pallet designed with the special size 1200 x 1200 mm
- Ideal for high-rotation usage such as open or closed pools
- Excellent transport for six modular units (600 x 400 mm) per layer
- 4. Big bags (FIBC) can be handled and stored in racks safely
- Suitable for block stacking
- Various anti-slip options are available 6.
- Reusable pallet made of recycled plastic and 100% recyclable

Safety rims

- Anti-slip strips on deck and grommets under deck
- RFID transponders and other IoT options
- 4. Specific colors on request
- Individual marking and labeling
- ESD prevention: conductive and anti-static
- 7. Further bottom version: 3 runners
- Also available with closed deck