


Eco C5

OD-3R



43.3 x 43.3 in
1100 x 1100 mm

| Technical Data | Bottom support | Top Deck | Dimensions (in) / (mm) | Maximum Load Capacities (lbs) / (kg) | | | Weight (lbs) / (kg) | | |
|----------------|----------------|----------|------------------------|--------------------------------------|---------|---------|---------------------|----|----|
| | | | | Static | Dynamic | Racking | PE | PP | PO |
| Eco C5 (OD-3R) | 3 runners | open | 43.3 x 43.3 x 5.9 | 6200 | 3100 | 600 | 27,5 | - | - |
| | | | 1100 x 1100 x 150 | 2800 | 1400 | 250 | 12,5 | - | - |

Entry: 4 ways | Nesting height: - inch / - mm | Safety rim: 0.28 in / 7 mm

| Logistic Data | Standard Truck Europe | | Standard Truck USA | | Mega Truck | | Jumbo Truck | | 40' HC Container | |
|----------------|-----------------------|-------|--------------------|-------|------------|-------|-------------|-------|------------------|-------|
| | stack | total | stack | total | stack | total | stack | total | stack | total |
| Eco C5 (OD-3R) | 16 | 384 | - | - | 19 | 456 | - | - | 17 | 340 |

Benefits

1. Economic solution with excellent performance-weight ratio
2. Designed with reinforced corners for increased impact resistance
3. Rounded edges to optimize the protection of transported goods
4. Easy to clean and dry
5. Reusable pallet made of recycled plastic and 100% recyclable

Options

1. Safety rim of 7 mm
2. Grommets under deck
3. RFID transponders and other IoT options
4. Specific colors on request
5. Individual marking and labeling
6. ESD prevention: conductive and anti-static
7. Further bottom version: 6 runners