Cabka

Eco US5

CD-3R

48 x 40 in
1219 x 1016 mm

Technical Data	Bottom support	Top Deck	Dimensions (in) / (mm)	Maximum Load Capacities (lbs) / (kg)			Weight (lbs) / (kg)		
				Static	Dynamic	Racking	PE	PP	PO
Eco US5 (CD-3R)	3 runners	closed	48 x 40 x 6.1	8800	3300	2200	–	37.5	–
			1219 x 1016 x 155	4000	1500	1000	–	17,0	–

Entry: 4 ways | Nesting height: – inch / – mm | Safety rim: 0.2 in / 6 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40´ HC Container	
	stack	total	stack	total	stack	total	stack	total	stack	total
Eco US5 (CD-3R)	–	–	17	510	–	–	–	–	–	–

Benefits

1. Universal multi-trip pallet for applications in closed circuits, production plants and goods distribution
2. Designed to offer high performance and durability
3. High impact strength reduces the risk of damage, extending the service life
4. Perfectly suited for high racks
5. Reusable pallet made of recycled plastic and 100% recyclable

Options

1. Safety rim
2. Anti slip strips and grommets on and under deck
3. RFID transponders and other IoT options
4. Specific colors on request
5. Individual marking and labelling
6. HACCP-compliant PP with FDA approval (freezer additives available)