



Endur C7.2

CD-3R



44.9 x 44.9 in
1140 x 1140 mm

| Technical Data | Bottom support | Top Deck | Dimensions (in) / (mm) | Maximum Load Capacities (lbs) / (kg) | | | Weight (lbs) / (kg) | | |
|--------------------|----------------|----------|------------------------|--------------------------------------|---------|---------|---------------------|------|----|
| | | | | Static | Dynamic | Racking | PE | PP | PO |
| Endur C7.2 (CD-3R) | 3 runners | closed | 44.9 x 44.9 x 6.5 | 11000 | 5500 | 2800 | 55.0 | 53.0 | - |
| | | | 1140 x 1140 x 165 | 5000 | 2500 | 1250 | 25,0 | 24,0 | - |

Entry: 4 ways | Nesting height: - inch / - mm | Safety rim: 0.3 in / 7 mm

| Logistic Data | Standard Truck Europe | | Standard Truck USA | | Mega Truck | | Jumbo Truck | | 40' HC Container | |
|--------------------|-----------------------|-------|--------------------|-------|------------|-------|-------------|-------|------------------|-------|
| | stack | total | stack | total | stack | total | stack | total | stack | total |
| Endur C7.2 (CD-3R) | 15 | 330 | - | - | 18 | 382 | 18 | 432 | 16 | 330 |

- Benefits**
1. Developed for transport in ISO freight containers
 2. Robust design to maximize inherent impact resistance
 3. Ability to carry loads up to 1250 kg in the high rack
 4. Ideal for use in automated conveyor systems
 5. Various anti-slip options are available
 6. Reusable pallet made of recycled plastic and 100% recyclable

- Options**
1. Safety rims
 2. Anti-slip strips on deck and grommets under deck
 3. RFID transponders and other IoT options
 4. Specific colors on request
 5. Individual marking and labeling
 6. ESD: conductive and anti-static
 7. Further bottom version: 6 runners
 8. Also available with open deck