



Endur i7.2

OD-3R

Benefits

47.2 x 39.4 in 1200 x 1000 mm

	Technical Data	Bottom support	Top Deck	Dimensions (in) / (mm)	Maximum Load Capacities (lbs)/(kg)				Weight (Ibs) / (kg)		
					Static	Dynamic	Racking	PE	PP	РО	
	Endur i7.2 (OD-3R)	3 runners	open	47.2 x 39.4 x 6.3	13200	4400	2200	-	44.0	-	
				1200 x 1000 x 160	6000	2000	1500	-	20,0	-	

Entry: 4 ways | Nesting height: - inch / - mm | Safety rim: 0.3 in / 7 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40′ HC Container	
Logistic Data	stack	total	stack	total	stack	total	stack	total	stack	total
Endur i7.2 (OD-3R)	15	390	-	-	17	442	17	476	16	352

Options

1. Optimal material handling with anti-slip options, grommets and safety rim

 \equiv

- 2. Special shock absorbent design improves impact resistance
- 3. Specially designed for high racking loads
- 4. Robust pallet with low damage rates
- 5. Hygenic design with no dirt traps
- 6. Virgin and recycled plastic option available for a sustainable approach
- 7. Reusable pallet made of recycled plastic and 100% recyclable

- 1. Safety rims
 - 2. Anti-slip strips on deck and grommets under deck
- 3. Specific colors on request
 - 4. Individual marking and labeling
 - 5. ESD: anti-static

US 2023-11-06