









Endur i7

OD-6R



















Technical Data	Bottom support	Top Deck	Dimensions (in) / (mm)	Maximum Load Capacities (lbs) / (kg)				Weight (lbs) / (kg)		
				Static	Dynamic	Racking	PE	PP	РО	
Endur i7 (OD-6R)	6 runners	open	47.2 x 39.4 x 6.3	13200	5500	3000	-	49.5	-	
			1200 x 1000 x 160	6000	2500	1375	-	22,5	-	

Entry: 4 ways | Nesting height: - inch / - mm | Safety rim: 0.3 in / 7 mm

Logistic Data	Standard Truck Europe		Standard Truck USA		Mega Truck		Jumbo Truck		40' HC Container	
Logistic Data	stack	total	stack	total	stack	total	stack	total	stack	total
Endur i7 (OD-6R)	15	390	-	-	17	442	17	476	16	342

- Designed to maximize impact resistance
- Excellent performance in high-rotation usage
- Exceptional bending strength, ideal for roller conveyors and high rack
- 4. Easy to clean and dry, perfect for semi-hygienic applications
- 5. Feet with rounded corners to optimize the use with forklifts
- Reusable pallet made of recycled plastic and 100% recyclable

Options Safety rims

- Anti-slip strips and grommets on and under deck
- RFID transponders and other IoT options
- 4. Specific colors on request
- 5. Individual marking and labeling
- ESD: conductive and anti-static