


Eco i5

OD-5R


1200 x 1000 mm



| Technical Data | Bottom support | Top Deck | Dimensions (mm) | Maximum Load Capacities (kg) | | | Weight (kg) | | |
|----------------|----------------|----------|-------------------|------------------------------|---------|---------|-------------|--------|--------|
| | | | | Static | Dynamic | Racking | PE | PE Mix | PP Mix |
| Eco i5 (OD-5R) | 5 runners | open | 1200 x 1000 x 150 | 4000 | 1750 | 600 | 13,5 | 13,5 | 14,5 |

Entry: 4 ways | Nesting height: - mm | Safety rim: 6,5 mm

| Logistic Data | Standard Truck Europe | | Standard Truck USA | | Mega Truck | | Jumbo Truck | | 40' HC Container | |
|----------------|-----------------------|-------|--------------------|-------|------------|-------|-------------|-------|------------------|-------|
| | stack | total | stack | total | stack | total | stack | total | stack | total |
| Eco i5 (OD-5R) | 16 | 416 | - | - | 19 | 494 | 19 | 532 | 17 | 374 |

Benefits

1. High performance at low cost
2. Monoblock design with impressive weight/load ratio
3. Ideal for closed loops, distribution, production areas and export
4. Strong performance with roller conveyors and in high racks
5. Flow-through block design ensures effective cleaning and quick drying
6. Rounded corners to reduce potential fork access damage
7. Reusable pallet made of recycled plastic and 100% recyclable

Options

1. Safety rim
2. RFID transponders and other IoT options
3. Specific colors on request
4. Individual marking and labelling
5. ESD: anti-static