

## CabCube® 3.0

9 Feet





1235 x 830 x 954 mm







Technical Data	Bottom	External	Internal Dimensions (mm)	Maximum Load Capacities (kg)		
lechnical Data	support	Dimensions (mm)		Stacking	Dynamic	Racking
CabCube® 3.0 (9F)	9 feet	1235 x 830 x 954	1190 x 785 x 773	1500	500	-

- Optimal for stacking stability and fit
- Great foldability ratio
- Ergonomic design with optimal handling through handles on the lid and easy sleeve attachment
- Secured folded unit with protected sleeve
- Reinforced feet for maximum impact resistance
- Large hatch for easy access to stored goods
- Reusable product, 100% recyclable, base and lid made of recycled plastic

- Repairable/interchangeable feet
  - Grommets under the base
  - RFID transponders and other IoT options
  - Customizable sleeve dimensions
  - Customizable sleeve design
  - Individual marking and labeling
  - ESD: conductive
  - Two further base options available (3 Runners, 4 Feet)





# CabCube® 3.0

9 Feet







1235 x 830 x 954 mm


Standard Components	Base	Sleeve (optional)	Lid
or and a second			
Weight	24,0 kg	9,6 kg	7,7 kg
Material	PE	PP	PE
Dimensions	1235 x 830 x 187 mm	1208 x 803 x 800 mm	1235 x 830 x 69 mm

Technical Data	CabCube® 3.0 9 feet	
Filling Volume	722 L	
Height of folded box	239 mm	
Nesting Space	26 mm	
Weight	41 kg	
Entries	4 way	
Sleeve Thickness	10 mm	
Sleeve Density	3000 gr/m <sup>2</sup>	

Maximum Load Capacities	
Filling weight	500 kg
Stacking load	1500 kg
Stacking factor	1+5
Dynamic load	500 kg

Truck Loads	<b>Mega Truck</b> (13,6 x 2,48 x 3,0 m)	
unfolded per stack	3	
unfolded total	96	
folded per stack	13	
folded total	416	
Return ratio	1: 4,3	
Volume reduction	77 %	

### Stacking scenarios



in Mega Truck

**Return Ratio** 1:4,3









### Megatrailer utilization

Full containers 44 (6)

